

# Economy class price First Class features



**GOGO**<sup>®</sup>  
**ULTRA X**

The Go-Go Ultra X is loaded with features such as one-hand disassembly and a convenient drop-in battery box for worry-free travel. With a 117 kg weight capacity, a maximum speed up to 6,4 km/h, a per-charge range up to 11 km on the 3-wheel and 11,6 on the 4-wheel, Go-Go Ultra X is an exceptional value.




Feather-Touch Disassembly

**PRIDE**<sup>®</sup>  
MOBILITY  
LIVE YOUR BEST<sup>®</sup>

## Specifications

3W: S40X 4W: S44X

WEIGHT CAPACITY	117 kg
MAXIMUM SPEED <sup>1</sup>	Up to 6,4 km/h
GROUND CLEARANCE <sup>2</sup>	3W: 78 mm 4W: 76 mm
TURNING RADIUS	3W: 838 mm   4W: 1117 mm
OVERALL LENGTH <sup>2</sup>	3W: 940 mm   4W: 1003 mm
OVERALL WIDTH <sup>2</sup>	495 mm
SEAT-TO-DECK HEIGHT	400 - 438 mm
SEAT-TO-GROUND HEIGHT	463 - 514 mm
FRONT TIRES	3W: 2" x 8" solid   4W: 2" x 7" solid
REAR TIRES	2.5" x 8" solid
RANGE PER CHARGE <sup>1,4</sup>	3W: Up to 11 km 4W: Up to 11,6 km
TOTAL WEIGHT WITHOUT BATTERIES	3W: 34,5 kg   4W: 36,3 kg
HEAVIEST PIECE WHEN DISASSEMBLED	3W: 13,1 kg (front section) 4W: 15,4 kg (front section)
STANDARD SEATING	Type: Foldable, compact, vinyl-covered, molded plastic Weight: 10,4 kg Material: Black Vinyl Size: 432 x 432 mm (width x depth)
MOTOR OUTPUT	24-volt DC motor, sealed mini-transaxle
BRAKES	Regenerative and electromechanical
BATTERY REQUIREMENTS <sup>3,5</sup>	Size: (2) 12 AH, 4 kg each Weight: 12 AH: 9 kg per battery pack
BATTERY CHARGER	2 amp, off-board
COLORS	 Red

## Features

- Convenient dual voltage charger can charge battery pack on-board or off-board
- Feather-touch disassembly permits simple frame separation with only one hand and easily disassembles into five super lightweight pieces for convenient transport and storage
- Front frame-mounted seat post offers maximum stability
- Pride's exclusive black, non-scuffing tires

## Accessories

- Cane/crutch holder (single, double)
- Cup holder
- Double crutch holder
- Forearm crutch holder
- Oxygen tank holder
- Quad cane holder
- Rear basket
- Saddlebag
- Safety flag
- Under seat storage (assembly required)
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger

## Options

- Battery pack

<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

<sup>2</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3%.

<sup>3</sup> AGM or gel cell type required.

<sup>4</sup> Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

<sup>5</sup> Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 series EN12184 standards.