

Outdoor Adventure awaits



RANGER



Backup sensors with LED light



Front lights



Tiller adjustment lever

Rugged and built to last; the Ranger is everything you want in an outdoor scooter! Equipped with front and rear suspension, this aggressive scooter is designed for cruising on walking trails or driving around your property. Enjoy total visibility with complete LED lighting. With a user-friendly console and dual hydraulic brakes for added safety, the Ranger is the perfect way to embrace life in the great outdoors!



PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]



Specifications

MV600

Features

WEIGHT CAPACITY	159 kg
MAX. SPEED ¹	Up to 17,7 km/h at 160 kg Up to 18,3 km/h at 90 kg
GROUND CLEARANCE ²	140 mm
TURNING RADIUS ²	2406 mm
LENGTH ²	1556 mm
WIDTH ²	826 mm
SEAT-TO-FLOOR HEIGHT	762 - 800 mm
FRONT TIRES	14,5" tubeless pneumatic
REAR TIRES	14,5" tubeless pneumatic
SUSPENSION	Front and rear (CTS suspension)
RANGE PER CHARGE ^{1,4}	Up to 30 km at 159 kg Up to 36 km at 91 kg
TOTAL WEIGHT WITHOUT BATTERIES	124 kg
HEAVIEST PIECE WHEN DISASSEMBLED	99 kg (unit does not disassemble)
STANDARD SEATING	Type: Pillow-top, limited recline Weight: 22 kg Material: Black vinyl Dimensions: Width: 470 mm, Depth: 419 mm
MOTOR OUTPUT	24-volt DC motor, rear-wheel drive, dual in-line
BRAKES	Regenerative and electromechanical
BATTERY REQUIREMENTS ^{3,6}	Size: (2) 75 AH Weight: 22 kg each
BATTERY CHARGER	5-amp, off-board
COLORS	 Dessert Storm  Stone Grey

- User friendly LED console displays time, temperature, miles driven and trips taken
- Adjustable delta tiller with ergonomic, wraparound handles
- USB charger built into the tiller for convenient charging of smart phones and portable devices
- Durable and stylish rear bumper
- Easily accessible tie-down points (for transport of unoccupied scooter)
- Full LED lighting package includes headlights, hazard lights, rear backup sensor LED lights and directional signals
- XLR charging port on tiller
- Hydraulic hand brake

Options

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder
- Weather cover
- Saddlebag
- Cell phone holder

1) Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
 2) Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3%.
 3) AGM or gel cell type required.
 4) Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and rive system performance. Test conducted at maximum weight capacity.
 5) Incl. standard seat
 6) Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressure, ambient temperature, and the gradient and surface of the road or pavement.