

Rugged with feather-touch disassembly





Experience the Revo® 2.0, a rugged scooter that combines an array of features into one great package. Tough and built to last, the Revo 2.0 offers rugged dependability you expect from luxury mid-size scooters. Comfort-Trac Suspension (CTS) ensures a smooth and comfortable ride over varied terrain. Experience convenient, feather-touch disassembly for portability that is comparable to our Travel Mobility line. Enjoy standard under seat storage and speeds up to 8 km/h. Ride on with the Revo 2.0!

PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

Specifications

S67

WEIGHT CAPACITY	170 kg
MAXIMUM SPEED	8 km/h
UNDER DECK CLEARANCE	88 mm
GROUND CLEARANCE	32 mm
TURNING RADIUS	1321 mm
OVERALL LENGTH	1194 mm
OVERALL WIDTH	527 mm
SEAT-TO-GROUND HEIGHT	597 mm highest position; 533 mm lowest position
SEAT-TO-DECK HEIGHT	457 mm
FRONT TIRES	3" x 9"
REAR TIRES	3" x 9"
SUSPENSION	Front and rear
DRIVE SYSTEM	Two-motor, 24 volt DC motor
DUAL BRAKING SYSTEM	Regenerative and electro-mechanical
RANGE PER CHARGE ^{1,2}	Up to 21 km
TOTAL WEIGHT WITHOUT BATTERIES ^{3,5}	60 kg
HEAVIEST PIECE WHEN DISASSEMBLED ³	25,9 kg (front section)
STANDARD SEATING	Dimensions: Width: 508 mm Depth: 457 mm
BATTERY REQUIREMENTS ⁴	(2) U1 batteries; 11,5 kg each
BATTERY CHARGER	3.5 amp
COLOR	 Grey Street  True Blue

Features

- Comfort-Trac front and rear suspension
- Durable and stylish rear bumper
- Easy accessible tie down points (for transport of unoccupied scooter)
- Easy adjustable tiller
- Easily charge the batteries on or off the unit
- Seat designed for extreme comfort
- Standard front basket
- Standard under seat storage
- Ultra heavy-duty drivetrain with
- 70 amp controller
- User-friendly console
- USB mobile device charging port

Accessories

- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- 1270 mm lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Under seat storage (assembly required)
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and rive system performance. Test conducted at maximum weight capacity.

³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3%.

⁴ Battery weight may vary based on manufacturer.

⁵ Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.