

Supreme performance, exhilarating style and Excellent Value



Ruspension front





Suspension rear

The sleek, sporty Victory® 10 DX Scooter delivers smooth performance and all-new features. With a full complement of advanced standard features including rugged suspension, a high-visibility automatic front and rear lighting system, feather-touch disassembly, an LED kerb light, and a wraparound delta tiller, the Victory 10 DX is a greater value than ever before.



Specifications 3W: SC610DX 4W: SC710DX

WEIGHT CAPACITY	159 kg
MAX SPEED ¹	Up to 10 km/h
GROUND CLEARANCE ²	82 mm
TURNING RADIUS ²	3W: 1067 mm 4W: 1333 mm
OVERALL LENGTH ²	3W: 1187 mm 4W: 1194 mm
OVERALL WIDTH ²	562 mm
FRONT TIRES	3.5" x 10" solid
REAR TIRES	4" x 10" solid
SUSPENSION	Front and rear
RANGE PER CHARGE ^{2,4}	Tot 25 km
TOTAL WEIGHT WITHOUT BATTERIES	3W: 81 kg 4W: 84 kg
HEAVIES PIECE WHEN DISASSEMBLED	3W: 25 kg (front) 4W: 29,48 kg (rear)
STANDARD SEATING	Type: High back with sliders Weight: 25 kg Material: Black vinyl Size: 430 mm x 430 mm
DRIVE SYSTEM	Rearwheel drive, sealed transaxle, 24-volt DC motor
DUAL BRAKING SYSTEM	Regenerative and electromechanical
BATTERIES ^{3,5}	2x12-volt, deep cycle Size: U-1 (31-36 AH) (standard) 40 AH (optional) Gewicht: U-1 (31-36 AH): 11 kg each; 40 AH: 14,74 kg each
CHARGER	5-amp, off-board
COLOURS	  Rood Blauw

Features

- Limited front & full rear suspension
- High visibility automatic front & rear lighting system
- Exclusive one-hand feather-touch disassembly provides the ultimate quick transport system
- Long-lasting, high intensity LED headlight, tail light & indicators
- Auto-connecting front-to-rear harness
- Delta tiller with wraparound handles
- New backlit battery meter for increased accuracy & visibility in any setting
- CRS high-back seat with headrest
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port for standard dual voltage off-board charger
- Rearview mirror standard
- Seat post suspension standard

Options

- Cane/crutch holder
- Oxygen holder
- Rear basket
- Extra rearview mirror

- ¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition.
- ² These specifications can be subject to a variance of (+/- 10%).
- ³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3%.
- ⁴ AGM or gel cell type required.
- ⁵ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and rive system performance. Test conducted at maximum weight capacity.
- ⁶ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Pride Mobility Products Europe BV

De Zwaan 3
1601 MS Enkhuijzen
The Netherlands

Tel: +31 (0)85-0408630 • Fax: +31 (0)85-0430039
pridemobility.eu • info@prideeurope.nl