

Small, Light and Portable




GO CHAIR®

The Go Chair® is #1 for portability! With convenient feather-touch disassembly, the Go Chair® allows you to experience lightweight travel and independence on the go. Enjoy dual swing-away storage bins and a compact turning radius for outstanding maneuverability. Available in an array of contemporary colors, it's time to get out there with the Go Chair®!

PRIDE®
MOBILITY
LIVE YOUR BEST®

Specifications

WEIGHT CAPACITY	136 kg
MAXIMUM SPEED ¹	Up to 6 km/h
GROUND CLEARANCE ³	43 mm
TURNING RADIUS ³	648 with foot platform
OVERALL LENGTH ³	838 mm with front rigging
OVERALL WIDTH ³	648 mm
SEAT-TO-GROUND HEIGHT	559 - 584 mm
SEAT-TO-DECK HEIGHT	413 - 438 mm
FRONT TIRES	6" solid (caster)
REAR TIRES	9" solid (drive)
SUSPENSION	Limited
RANGE PER CHARGE	Up to 14 km standard, 17,5 km extended range
TOTAL WEIGHT WITHOUT BATTERIES ^{3,7}	30,4 kg (front & rear base)
HEAVIEST PIECE WHEN DISASSEMBLED ³	16 kg (rear)
STANDARD SEATING	Foldable, compact, lightweight 457 x 432 mm
DRIVE SYSTEM	Two-motor rear-wheel drive
DUAL BRAKING SYSTEM	Electronic, regenerative
BATTERY REQUIREMENTS ^{3,4,5}	(2) 18 AH, or (2) 18 AH extended range
BATTERY CHARGER	2-amp, off-board, 3.5 amp extended range
COLORS	 <p>Citrine Yellow Sapphire Blue Rose Quartz Amber Orange Pearl White Silver</p>

Features

- 457 x 444 mm, 5-point swivel seat with latch release
- Compact turning radius
- Dual swing-away, under seat storage bins
- Height and width adjustable armrests
- Large footplate
- One hand feather-touch disassembly
- 1524 mm lap belt
- The heaviest piece is only 16,3 kg

Accessories

- Armrest mount cane clip
- Cane/crutch holder (single, double)
- Cup holder
- Lap belt (1270 or 1778 mm)
- Oxygen tank holder
- Rear mount basket
- Saddlebag
- Safety flag
- Weather cover
- XLR USB charger

Options

- 18 AH extended range batteries
- Additional battery pack

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition tire type and condition. These specifications can be subject to a variance of + 10%, -5%.

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM or Gel-Cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA and ISO 7176 series standards. All specifications subject to change without notice.