

Outstanding maneuverability,
outdoor performance and
luxury features



The Pursuit® Sport 36 Volt Mobility Scooter offers the maneuverability of a 4-wheel mobility scooter along with high-performance features like 36 volts of power, full suspension and a hydraulic sealed brake system. The Pursuit Sport 36 Volt features sleek, aggressive style and a wealth of standard luxury touches including a wraparound delta tiller and LED lighting, making it the ultimate outdoor scooter.



PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]



Specifications

MV714

Features

WEIGHT CAPACITY	181 kg
MAXIMUM SPEED ¹	Up to 20 km/h
GROUND CLEARANCE ²	63 mm
TURNING RADIUS	2083 mm left / 2108 mm right
OVERALL LENGTH ²	1420 mm
OVERALL WIDTH ²	692 mm
FRONT TIRES	13" pneumatic
REAR TIRES	13" pneumatic
SUSPENSION	Front and rear
RANGE PER CHARGE ¹	Up to 36,3 km
TOTAL WEIGHT WITHOUT BATTERIES	123 kg (without seat or batteries)
HEAVIEST PIECE WHEN DISASSEMBLED	98 kg
STANDARD SEATING	Type: Deluxe High-back seat with sliders Weight: 25 kg Material: Black Vinyl Dimensions: Width: 480 mm Depth: 430 mm
DRIVETRAIN	Rear-wheel drive, sealed transaxle, 36-volt DC motor
BRAKES	Electro-magnetic with drum brake system
BATTERY REQUIREMENTS ³	(3) 12-volt, deep cycle Size: (3) 55 AH Weight: 17.24 kg each
BATTERY CHARGER	8-amp, 36V off-board
COLORS	  Red Silver

- Full suspension for optimal handling
- Deluxe reclining high-back seat with headrest and sliders
- Enhanced tiller with wraparound handles and console
- Full LED-lighting package
- 36 volt battery system with (3) 12-volt 55 AH batteries

Accessories

- Cell phone holder
- Cup holder
- 1270 mm lap belt
- Rear basket
- Rear view mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover
- XLR USB charger

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.