

Advanced engineering for powerful performance and exceptional style



VICTORY *XL 140*



Bristling with high-performance features like full suspension, low-profile tires and a hydraulic sealed brake system, the Victory® XL 140 is a blend of power and precision. The Victory® XL 140 features sleek style and a wealth of standard luxury touches like a wraparound delta tiller, new double A-arm suspension, new terrain gripping pneumatic tires and LED lighting, making it the ultimate outdoor scooter.







Full suspension

PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

Specifications

SC714

Features

WEIGHT CAPACITY	181 kg
MAX. SPEED ¹	Up to 15 km/h
GROUND CLEARANCE ²	13,33 cm
TURNING RADIUS ²	2108 mm (right) / 2083 mm (left)
LENGTH ²	1428 mm
WIDTH ²	692 mm
FRONT TIRES	4" x 13" pneumatic
REAR TIRES	4" x 13" pneumatic
SUSPENSION	Front and rear
RANGE ^{1,5}	100 AH Batterijen: Standard: Up to 46,5 km Optional: Up to 42,2 km
TOTAL WEIGHT WITHOUT BATTERIES	117,70 kg
HEAVIEST PIECE WHEN DISASSEMBLED	Frame: 93,21 kg
STANDARD SEATING	Type: Foldable Weight: 21,77 kg Material: Black vinyl Size: width - 495 mm depth - 444 mm height - 470 mm
DRIVE	Rear-wheel drive, sealed transaxle 24-volt DC motor
DUAL BRAKING SYSTEM	Regenerative and electromechanical
BATTERIES ³	2 (12 V) Size: Groep 31 (100 AH) Weight ⁴ : 27,44 kg
BATTERY CHARGER	8-amp, off-board
COLORS	 Red  Blue  Black  Silver

- New Double A-Arm Suspension for optimum handling
- Sealed hydraulic brakes
- New large 13" terrain gripping pneumatic tires for excellent outdoor performance
- Full lighting package including directional signals and lower headlight
- Delta tiller with wraparound handles
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror standard

Options

- Front shield
- Pillow top
- Double crutch holder
- Oxygen tank holder
- Rear basket
- Additional rearview mirror

1) Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

2) Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

3) Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3%.

4) AGM or gel cell type required.

5) Battery weight may vary based on manufacturer.

6) Incl. standard seat

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressure, ambient temperature, and the gradient and surface of the road or pavement.