Rugged with feather-touch disassembly





Experience the Revo 2.0, a rugged scooter that combines an array of features into one great package. Tough and built to last, the Revo 2.0 offers rugged dependability you expect from luxury mid-size scooters. Comfort-Trac Suspension (CTS) ensures a smooth and comfortable ride over varied terrain. Experience convenient, feather-touch disassembly for portability that is comparable to our Travel Mobility line. Enjoy standard under seat storage and speeds up to 8 km/h.

Ride on with the Revo 2.0!





Specifications

S67

WEIGHT CAPACITY	170 kg
MAXIMUM SPEED ¹	8 km/h
GROUND CLEARANCE ²	32 mm
TURNING RADIUS ²	1321 mm
OVERALL LENGTH ²	1194 mm
OVERALL WIDTH ²	527 mm
FRONT TIRES	3-wheel: 8" solid or pneumatic 4-wheel: 9" solid or pneumatic
REAR TIRES	9" solid or pneumatic
DRIVE SYSTEM	Rear-wheel drive, sealed transaxle, 24-volt DC motor
DUAL BRAKING SYSTEM	Elektromechanic
RANGE PER CHARGE ^{1,4}	3-wheel solid tires: Up to 21,2 km at 170 kg Up to 28 km at 91 kg 3-wheel pneumatic tires: Up to 16,5 km at 170 kg Up to 23,6 km at 91 kg 4-wheel solid tires: Up to 20 km at 170 kg Up to 28,6 km at 91 kg 4-wheel pneumatic tires: Up to 19,5 km at 170 kg Up to 26,1 km at 91 kg
TOTAL WEIGHT WITHOUT BATTERIES 5	3-wheel: 54,25 kg 4-wheel: 59,75 kg
STANDARD SEATING	Type: Molded Plastic Material: Black Vinyl Width: 508 mm- 432 mm Depth: 457 mm - 432 mm Weight: 12.25 kg
BATTERY REQUIREMENTS ⁴	Type: Two 12-volt, sealed lead-acid, non-spillable deep-cycle Size: U1
BATTERY CHARGER	3.5 amp off-board charger
COLOR	Grey True Street Blue

Features

- Comfort-Trac front and rear suspension
- Durable and stylish rear bumper
- Easy accessible tie down points (for transport of unoccupied scooter)
- Easy adjustable tiller
- Easily charge the batteries on or off the unit
- Seat designed for extreme comfort
- Standard front basket
- Standard under seat storage
- Ultra heavy-duty drivetrain with
- 70 amp controller
- User-friendly console
- USB mobile device charging port

Accessories

- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- 1270 mm lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Under seat storage (assembly required)
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger
- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

 2 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specificateions and rive system performance. Test conducted at maximum weight capacity.

 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or 3%.

 4 Battery weight maximum.
- 4 Battery weight may vary based on manufacturer.
- 5 Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



De Zwaan 3 1601 MS Enkhuizen The Netherlands