

A Smooth Ride for your active lifestyle



VICTORY[®] 10
LX WITH CTS SUSPENSION

CTS SUSPENSION



Front suspension






Rear suspension

The Victory 10 LX with CTS Suspension offers a smooth ride with performance to match. Comfort-Trac Suspension (CTS) is the next generation in mobility scooter ride comfort. This industry first technology incorporates advanced suspension components for improved absorption over rough surfaces and a more comfortable ride experience over various terrains.

Specifications

S710LX

WEIGHT CAPACITY	181 kg
MAX. SPEED ¹	Up to 9 km/h
GROUND CLEARANCE ²	56 mm
TURNING RADIUS ²	1559 mm
LENGTH ²	1194 mm
WIDTH ²	565 mm
SEAT-TO-FLOOR HEIGHT	451 mm
TIRES	10" heavy-duty foam
SUSPENSION	Front and rear
RANGE PER CHARGE ^{1,5}	Up to 26 km
TOTAL WEIGHT WITHOUT BATTERIES	70,9 kg
HEAVIEST PIECE WHEN DISASSEMBLED	35,2 kg (front section)
STANDARD SEATING	Type: Folded Moldable Plastic Weight: 12.5 kg Material: Black Vinyl Width: 457 mm Depth: 457 mm
MOTOR OUTPUT	Rear-wheel drive, sealed transaxle, 24-volt DC motor
BRAKES	Regenerative and electromechanical
BATTERY REQUIREMENTS ³	Type: Two 12-volt, sealed lead-acid, non-spillable, deep-cycle Size: 32 Ah or 40 Ah (standard) 50 Ah (optional)
BATTERY CHARGER	5-amp, off-board
COLORS	 Red  Blue  White

Features

- Comfort-Trac front and rear suspension
- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- Delta tiller with wraparound handles
- Easy-to-read LED battery meter
- Exclusive stylish, lightweight, non-scuffing, black, low-profile tires
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination with a courtesy light under tiller
- Black vinyl reclining high-back seat with sliders, height adjustable headrest, flip-up, height and width adjustable armrests
- Storage compartment below tiller
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port
- Auto-connecting front-to-rear harness

Options

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder
- Weather cover
- Saddlebag
- Cell phone holder
- Touch-up paint

1) Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

2) Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and rive system performance. Test conducted at maximum weight capacity.

3) Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3%.

4) AGM or gel cell type required.

5) Battery weight may vary based on manufacturer.

6) Incl. standard seat

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressure, ambient temperature, and the gradient and surface of the road or pavement.