

The compact design of the Go-Go Elite Traveller allows you to easily manoeuver in tight spaces while providing stable outdoor performance. With a 136 kg weight capacity, a charger port in the tiller, one-hand feathertouch disassembly and maximum speeds up to 6,4 km/h, it's easy to go where you want to go!





## **Specifications**

3W: SC40F 4W: SC44F

Weight capacity	136 kg
Max. speed <sup>1</sup>	Up to 6,4 km/h
Ground clearance <sup>2</sup>	35 mm
Turning radius <sup>2</sup>	3W: 838 mm   4W: 1120 mm
Length <sup>2</sup>	3W: 940 mm   4W: 1003 mm
Width <sup>2</sup>	495 mm
Front tires	3W: 8" solid   4W: 7" solid
Rear tires	8" solid
Max. range per charge <sup>1,4</sup>	3W: Up to 16,7 km 4W: Up to 15,6 km
Total weight without batteries <sup>5</sup>	3W: 34,2 kg   4W: 36 kg
Standaard seat <sup>2</sup>	Type: Folded Material: Black Vinyl Width: 432 mm Depth: 432 mm Weight: 10.2 kg
Drive system	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Brakes	Regenerative and electromechanical
Batteries	Type: Two 12-volt, deep-cycle Capacity: 12 Ah Weight: 8,75 kg
Standard colors	Red Blue

- Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%). Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or 3%. AGM or gel cell type required. Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specificateions and rive system performance. Test conducted at maximum weight capacity. Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3%. Dimensions listed are for scooter only. Overall measurements will vary based on

## **Features**

- Charger port in tiller
- Convenient dual voltage charger can charge battery pack on-board or offboard
- Feather-touch disassembly permits simple frame separation with only one hand and easily disassembles into five lightweight pieces for convenient transport and storage
- Front frame-mounted seat post offers maximum stability
- Front tiller-mounted basket
- Includes two sets of easily changeable, red and blue colored panels
- Microprocessor-based controller offers optimal power management and added safety features
- Pride's exclusive black, non-scuffing
- Removable footboard basket for additional storage (4-wheel version

## Accessories

- Cane/crutch holder (single, double)
- Cup holder
- Double crutch holder
- Forearm crutch holder
- Oxygen tank holder
- Quad cane holder
- Rear basket
- Saddlebag
- Safety flag
- Under seat storage (assembly required)
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger



