# Enjoy a Smooth and Sporty ride

Maintain your active lifestyle with the Victory® LX Sport. Equipped with Comfort-Trac Suspension (CTS), the Victory LX Sport easily handles more varied terrain while providing a smooth and comfortable ride. Enjoy convenient storage and a courtesy light under the tiller. A long-lasting LED headlight ensures optimal pathway illumination. Experience great features and a sporty style with the Victory LX Sport.





## **Specifications**

#### S710LXWFU

Weight capacity <sup>7</sup>	181 kg
Maximum speed <sup>1</sup>	Up to 13 km/h
Ground clearance <sup>2</sup>	56 mm
Turning radius <sup>2</sup>	1556 mm
Length <sup>2</sup>	895 mm
Width <sup>2</sup>	648 mm
Tires	10" solid
Drive system	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system	Regenerative and electromechanical
Range per charge <sup>1,4</sup>	Up to 32 km
Total weight without batteries ⁵	73 kg
Standard seating	Type: High Back Weight: 19,5 kg Material: Black Vinyl Width: 457 mm Depth: 457 mm
Batteries <sup>3,6</sup>	Qu'antity: 2 Type: Sealed lead-acid, deep cycle Size: 40 or 50 Ah
Battery charger	5 Amp, off-board
Colors	Red Blue

### **Features**

- CTS Suspension includes adjustable • shocks for greater comfort
- Exclusive one-hand feather touch disassembly
- Charger port located on the tiller lets you conveniently charge your scooter
- Delta tiller with ergonomic . wraparound handles lets you operate the scooter with one hand and rest your wrist
- . Easy-to-read LED voltmeter
- Rearview mirror

## Accessories

- Cane/crutch holder
- Cell phone holder
- . Cup holder
- Lap belt
- Oxygen tank holder
- Rear basket
- **Rearview mirror**
- Saddlebag .
- Safety flag
- Walker holder
- Weather cover

- 1
- 2.
- 3. 4.
- Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of +10%, -5%. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%. AGM or Gel-Cell type required. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity. Includes standard seat. Battery weight may vary based on manufacturer All measurements taken using standard seat.
- 5
- 6. 7.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + o - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



**Pride Mobility Products BV** De Zwaan 3 1601 MS Enkhuizen The Netherlands Tel: +31 (0)85-0408630 · Fax: +31 (0)85-0430039 pridemobility.eu · info@prideeurope.nl