# Excellent Outdoor Performance with Luxurious Features



The Pride Victory<sup>®</sup> Luna 3-wheel scooter gives a powerful performance for both in- and outdoor usage. Luxurious styling and comfort features like a foam delta tiller and non-marking tires make the Pride Victory<sup>®</sup> Luna an all in-one-package.





## **Specifications**

Weight capacity <sup>1</sup>	159 kg
Maximum speed <sup>1</sup>	Up to 15 km/h
Ground clearance <sup>2</sup>	95 mm
Turning radius <sup>2</sup>	1257 mm
Length <sup>2</sup>	895 mm
Width <sup>2</sup>	686 mm
Tires	13" pneumatic
Drive system	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system	Regenerative and electromechanical
Range per charge <sup>1,4</sup>	Up to 44 km
Total weight without batteries <sup>5</sup>	88 kg
Standard seat	Type: High Back Weight: 23 kg Material: Black Vinyl Width: 457 mm Depth: 483 mm
Batteries <sup>3</sup>	Quantity: 2 Type: Sealed lead-acid, deep cycle Size: Group 24 (75 Ah)
Battery charger	8 Amp, off-board
Colors	Red

1

- 2.
- 3. 4
- Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of +10%, -5%. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%. AGM or Gel-Cell type required. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity. Includes standard seat.
- 5

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

### **Features** SC613

- Large 13" pneumatic tires for excellent outdoor performance
- Full lighting package including directional signals and angleadjustable, LED head and tail lights
- Front basket standard •
- Easily accessible tie down points (for . transport of unoccupied scooter)
- Rearview mirror standard
- Easy throttle control by switchable push and pull lever
- Steady speed adjustment
- Tiller display operable with just one hand

# Accessories

- Cane/crutch holder
- Cell phone holder
- Cup holder
- Lap belt
- Oxygen tank holder .
- Rear basket
- Extra rearview mirror
- Saddlebag .
- Safety flag
- Walker holder
- Weather cover



**Pride Mobility Products BV** De Zwaan 3 1601 MS Enkhuizen The Netherlands Tel: +31 (0)85-0408630 · Fax: +31 (0)85-0430039 pridemobility.eu · info@prideeurope.nl