

With contemporary styling and cutting-edge technology, the Zero Turn 10 is the perfect combination of aggressive performance and maneuverability. Powerful dual motors and two-wheel drive offers aggressive traction, easily tackling rugged terrain on trails. When you're done spending time outdoors, the Zero Turn 10 transitions seamlessly indoors. Maneuver smoothly through halls and doorways with iTurn Technology.





## **Specifications**

S710ZT

Weight capacity	181 kg
Max speed <sup>1</sup>	Up to 10 km/h
Ground clearance <sup>2</sup>	51 mm
Turning radius <sup>2</sup>	1092 mm
Length <sup>2</sup>	1219 mm
Width <sup>2</sup>	613 mm
Tires	Front: 9" solid Rear: 10,75" solid
Range per charge <sup>1,4</sup>	Up to 30,4 km at 181 kg Up to 42,4 km at 91 kg
Total weight without batteries <sup>2,5</sup>	82,5 kg
Standard seating	Type: Molded Plastic Weight: 13,5 kg Material: Vinyl Width: 462 mm Depth: 410 mm
Drive system	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system	Regenerative and electromechanical
Batteries <sup>6</sup>	Quantity: 2 Type: Sealed lead-acid, deep cycle Size: 40 or 50 Ah
Battery charger	5 Amp, off-board
Colors	Pearl Ocean Candy White Blue Apple Red

## Standard features

- Three-speed control lets you adjust your speed when moving from indoor to outdoor driving
- Delta tiller with wraparound handles
- Easy access tiller-mounted charger
- USB charger built into the tiller for convenient charging of smart phones and portable devices
- Integrated storage/cup holder in the
- XLR charging port on tiller
- Standard front basket

## Accessories

- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- Lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Walker holder
- Weather cover

- Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of +10%, -5%. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%. AGM or Gel-Cell type required. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- at maximum weight capacity.
  Includes standard seat.
  Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.



