

Small, light and Portable




GO CHAIR®

The Go Chair is #1 for portability! With convenient feather-touch disassembly, the Go Chair allows you to experience lightweight travel and independence on the go. Enjoy dual swing-away storage bins and a compact turning radius for outstanding maneuverability. Available in an array of contemporary colors, it's time to get out there with the Go Chair!

PRIDE®
MOBILITY
LIVE YOUR BEST®

Specifications

| | |
|---|---|
| Weight capacity | 136 kg |
| Maximum speed ¹ | Up to 6 km/h |
| Ground clearance ² | 45 mm |
| Turning radius ² | 645 mm |
| Length ^{2,6} | 838 mm without front rigging 660 mm with front rigging |
| Width ^{2,6} | 574 mm |
| Drive wheels | 9" solid |
| Rear wheels | 6" solid |
| Anti-tip wheels | 3" solid |
| Suspension | Limited |
| Range per charge ^{1,4,6} | Up to 20,2 km |
| Heaviest piece when disassembled ^{4,5} | 16,5 kg (rear) |
| Standard seating | Type: Foldable, compact, lightweight Size: 457 x 432 mm Weight: 13,75 kg |
| Dual braking system | Intelligent braking (Electronic regenerative, disc park brake) |
| Battery requirements ^{3,5} | Quantity: 2 Type: Sealed lead-acid, deep cycle Size: 18 or 22 Ah Weight: 5,25 kg |
| Battery charger | 2 Amp off-board |
| Colors |  <div> Citrine Yellow Sapphire Blue Rose Quartz Amber Orange Pearl White Ruby Red </div> |

Features

- One hand feather-touch disassembly
- Its heaviest piece weights only 16,3 kg
- 457 x 444 mm, 5-point swivel seat with latch release
- Compact turning radius
- Dual swing-away, under seat storage bins
- Height and width adjustable armrests
- Large footplate
- Standard lap belt

Accessories

- Cane/crutch holder
- Cup holder
- Oxygen tank holder
- Rear mount basket
- Saddlebag
- Safety flag
- Weather cover
- XLR USB charger

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition tire type and condition. These specifications can be subject to a variance of + 10%, -5%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. AGM or Gel-Cell type required.
4. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
5. Battery weight may vary based on manufacturer.
6. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.