

Outstanding manoeuvrability
outdoor performance
and luxury features



ZOLAR

The Zolar Scooter offers the manoeuvrability of a 3-wheel scooter along with high-performance features like full suspension and a hydraulic sealed brake system. The Zolar features sleek, aggressive style and a wealth of standard luxury touches including a wraparound delta tiller and LED lighting, making it the ultimate outdoor scooter.


PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

ZOLAR

Specifications

SC614

Features

Weight capacity	181 kg
Maximum speed ¹	Up to 15 km/h
Ground clearance ²	70 mm
Turning radius ²	1273 mm
Length ²	1397 mm
Width ²	692 mm
Front tires	13" pneumatic
Rear tires	13" pneumatic
Drive system	Rear wheel drive, sealed transaxle, 24 Volt DC motor
Dual braking system	Regenerative and electromechanical
Range per charge ^{1,4}	Up to 37 km
Total weight without batteries ⁵	105 kg
Standard seating	Type: High back lumbar Material: Black Vinyl Width: 457 mm Depth: 483 mm Weight: 23 kg
Batteries ^{3,6}	Type: 2 12-volt, sealed lead-acid, non-spillable deep-cycle Size: Group 27 (92 Ah) Weight: 27,5 kg
Battery charger	5 amp off-board
Colors	 Silver

- Full suspension for optimal handling
- Large 13" pneumatic tires for excellent outdoor performance
- Full lighting package including directional signals and headlight
- Newly redesigned tiller with LCD console
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror standard

Accessories

- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- Lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover

1. Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of +10%, -5%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. AGM or Gel-Cell type required.
4. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
5. Includes standard seat.
6. Battery weight may vary based on manufacturer.
7. All measurements taken using 457.25 x 432 mm seat. Measurements may vary with use of different seating styles.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.