

# GO GO<sup>®</sup>

LX WITH CTS SUSPENSION



**PRIDE<sup>®</sup>**  
MOBILITY  
LIVE YOUR BEST<sup>®</sup>

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039  
pridemobility.eu . info@prideeurope.nl

The Go Go® LX with CTS suspension is a high-quality product with useful features, such as a delta handlebar, a high-placed charging connection, an LED headlight and a spacious basket at the front.



Comfort-Trac suspension



Disassembles into 5 pieces



Modular design for easy serviceability

## Specifications

Weight capacity	136 kg
Speed	Up to 7 km/h
Range per charge	3W: Up to 15,3 km 4W: Up to 17 km
Turning radius	3W: 851 mm 4W: 1162 mm
Ground clearance	36 mm
Length	3W: 1010 mm 4W: 1060 mm
Width	521 mm
Tires	3W: 8" solid front and rear 4W: 7" solid front, 8" solid back
Drive	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Weight without batteries	3W: 39 kg 4W: 41 kg
Batteries	Type: Two 12-volt, sealed lead-acid, non-spillable deep-cycle Size: 12 Ah or 18 Ah
More?	Download our specifications sheet on the website

## Features

- Feather-touch disassembly permits simple frame separation with only one hand
- Frame design easily disassembles into 5 lightweight pieces for convenient transport and storage
- Includes 2 sets of easily changeable colored panels in 2 colors – Red and Blue
- Charger XLR port incorporated in tiller allows charging without removing the battery box
- Microprocessor-based controller offers optimal power management and added safety features

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

## Available colors

