

PURSUIT²



PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039
pridemobility.eu . info@prideeurope.nl

With a top speed of 15 km/h and the ability to reach 56 km on a single charge, this agile unit offers fast, efficient transport and reliable endurance.



Infinitely adjustable tiller with USB charger



Enhanced LED lighting



Front and rear CTS suspension

Specifications

Weight capacity	159 kg
Speed	Up to 15 km/h
Range per charge	Up to 56 km
Turning radius	1760 mm
Ground clearance	96 mm
Length	1460 mm
Width	753 mm
Tires	13" pneumatic, front and rear
Drive	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Weight without batteries	100 kg
Batteries	Type: Two 25-volt lithium ion Size: 50 Ah
More?	Download our specifications sheet on the website

Features

- Durable plastic shrouds for navigating through brush, weather and transport
- Infinitely adjustable tiller with a USB charger to conveniently charge your devices on the go
- Pneumatic tires mounted on split rims for optimal handling and traction on every terrain you cruise through
- 99% of all maintenance can be carried out within 20 minutes
- 15 km/h top cruising speed for thrilling rides in the great outdoors

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Available colors

