

PRODUCT SPECIFICATIONS SHEET

Model: Victory XL 140 S (SC714)

Manufacturer: Pride Mobility Products Corp.

Internet Address: www.pridemobility.com

Document Information: INFINFB2693/Rev A/May 2011

Model Number	SC714
Maximum Obstacle Climbing Ability	12 cm (4,17 in.)
Maximum Allowable Incline	17,6% (10°)
Maximum Angle Capacity	17,6% (10°)
Overall Length²	142,8 cm (56,25 in.)
Overall Width²	69,2 cm (27,25 in.)
Total Weight	172,59 kg (380,5 lbs.)
Total Weight Without Batteries^{2, 5}	117,70 kg (259,5 lbs.)
Heaviest Piece When Disassembled²	Main frame: 93,21 kg (205,5 lbs.)
Turning Radius²	Right: 210,8 cm (83 in.), Left: 208,3 cm (82 in.)
Speed (Maximum)¹	20 km/h (12,42 mph)
Range Per Charge^{1, 4}	Up to 26,52 km (16,48 miles) with 92 Ah batteries Up to 21,42 km (13,31 miles) with 75 Ah batteries
Ground Clearance²	13,33 cm (5,25 in.)
Weight Capacity	136 kg (300 lbs.)
Standard Seating	Type: CRS Deluxe Weight: 21,77 kg (48 lbs.) Material: Black Vinyl Dimensions: 49,53 cm (19,5 in.) overall width 44,45 cm (17,5 in.) effective depth 47 cm (18,5 in.) height
Drive System	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual Braking System	Regenerative and electromechanical
Tires	Type: Solid and pneumatic available Front and rear: 33 cm (13 in.)
Battery Requirements^{3, 6}	Two 12-volt, deep-cycle Size: Group 27 (92 Ah) or Group 24 (75 Ah) Battery weight: 92 Ah: 27,44 kg (60,5 lbs.) each 75 Ah: 25 kg (55 lbs.) each
Battery Charger	8-amp, off-board
Freewheel Lever Operational Force	69 Newton meters (50,89 foot-pound force)

¹ Varies with user weight, terrain type, battery amp-hour (Ah), battery charge, battery condition and tire condition. This specification can be subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See IV. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Includes standard seat.

⁶ Battery weight may vary based on manufacturer.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.

