Model	Luna Victory Z1 Luna Victory Z2 Luna Victory Z3
Part number	Z1: SC123 Z2: SC133 Z3: SC143
Weight capacity ¹	159 kg
Maximum speed ¹	Up to 15 km/h
Ground clearance ²	90 mm at motor
Turning radius ²	1257 mm
Length ²	1425 mm ³
Width ²	670 mm
Tires	13" pneumatic or solid, front and back
Drive system	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system	Regenerative and electromechanical
Range per charge 1,5	Up to 30 - 45 km
Standard seat	Type: High Back Material: Black Vinyl
Batteries ⁴	Quantity: 2 Type: Sealed lead-acid, deep cycle Size: 50 or 75 Ah
Battery charger	Up to 8 Amp, off-board


Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of +10%, -5%

variance of +10%, -5%
Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%
With 130 length
AGM or Gel-Cell type required
Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical

calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.



Tel: +31 (0)85-0408630 | Fax: +31 (0)85-0430039 pridemobility.eu | info@prideeurope.nl









Steering wheel with pushpull or gas throttle lever LED lights and indicator

Protective bumpers all-round

Our all new **Luna Victory** is ready for the future; with its extremely high durability and premium quality this is the scooter that can and will fit all your needs. Designed for a 10-year life cycle, this commercial grade quality scooter is exceptionally reliable. This state-of-the-art scooter offers maximum flexibility; with different configurations to match exactly what the end user needs. The modularity combined with low maintenance forms the perfect scooter for a fleet owner.

STANDARD FEATURES

- Maximum configuration flexibility
- Designed to maximize longevity
- Comfortable dual suspension
- Optimized for reconditioning
- Maximum speed can be set between 10, 12 and 15 km/h, without programming
- Front basket standard
- Push pull or gas throttle lever
- 99% of all maintenance can be carried out within 20 minutes
- Protective bumpers all-round
- Motor protection program
- Connected Data Monitoring (optional)
- Steering wheel with push-pull lever or gas throttle switches

ACCESSORIES

- Cane/crutch holder
- Cell phone holder
- Cup holder
- Lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover